Shotgun Pack Instructions



Green Gun Oil

FOR EXTERNAL FIREARM TREATMENT: Apply a few drops to a gun patch, cloth or absorbent cotton and rub over entire metal surface of firearm. The metal's sheen will indicate the amount of coverage.

FOR INTERNAL OR BORE TREATMENT: Apply a few drops sufficient to saturate a gun patch and/or bore brush and insert in bore with a cleaning rod with a scrubbing motion.

FOR RECESSED PARTS: Apply a few drops directly to the recessed area and allow Green Gun Oil's wetting properties to penetrate the area.

Metcor 57 Gun Bore Cleaner

FOR INTERNAL OR BORE TREATMENT: Apply a few drops sufficient to saturate a gun patch and/or bore brush and insert in bore with a cleaning rod with a scrubbing motion.

FOR EXTERNAL FIREARM TREATMENT: Apply a few drops to a gun patch, cloth or absorbent cotton and rub over entire metal surface of firearm. The metal's sheen will indicate the amount of coverage.

FOR RECESSED PARTS: Apply a few drops directly to the recessed area and allow Metcor 57 Gun Bore Cleaner's wetting properties to penetrate the area.

Metcor 71 Duck Hunter's Delight

-Spray a light film of Metcor 71Duck Hunter's Delight over the entire metal surface of your firearm, including sights and trigger guard.

-For additional protection "swab-out" the bore of your firearm with a cleaning patch saturated with Metcor 71 Duck Hunter's Delight.



Green Leather Oil

Before applying Green Leather Oil to the entire item, apply to a small inconspicuous area to test compatibility depending on leather type. (Not intended for synthetic leather products)

-Clean any soil from leather before application with a mild soap and warm water. New leather requires no cleaning.

- -Apply with a clean, dry cloth, sponge, brush, or fingertips and massage into leather pores.
- -Allow leather article to absorb Green Leather Oil for several hours.

-Repeat steps 2 and 3 as necessary for severely dried or cracked leather items.



Green Stock Oil

-Using a soft, clean cloth, apply a small amount of Green Stock Oil to the wood surface. (Not *intended for sealed wood surfaces)*

- -Rub Green Stock Oil into the woods pores using a 2" circular pattern.
- -Continue to rub until you are satisfied with the woods sheen and overall appearance.
- -After application polish with a clean cloth if needed.



-Apply a few drops in the palm of the hand, add water and rub hands together then rinse to remove even the most difficult soil.

> 800.686.3201 1160 White Street Sturgis, MI 49091 www.metalloidfirearmsproducts.com



